AC Drain Line Overflow Kit

Setup & upkeep guide · While You're Away Co. · homewatchtreasurecoast.com

In the box

- YoLink Water Level Sensor (YS7904F) with float switch and 2 AAA batteries
- YoLink Hub (YS1603) with power adapter
- Poesie AC Drain Pan Tablets, 120 count

Parts ship from our fulfillment partner and may arrive in more than one box.

1. Set up the hub (5 minutes)

1. Install the free **YoLink** app (iPhone or Android) and create an account.
2. Plug the hub into an outlet near your router. Connect it by ethernet cable or follow the app to join Wi-Fi.
3. In the app tap **+** and scan the QR code on the hub.

2. Add the water level sensor

1. Pull the battery tab (or insert the 2 AAA batteries).
2. In the app tap **+** and scan the QR code on the sensor. Name it something clear, like "AC drain pan – hall closet".

3. Place the float

1. Find the drain pan under your air handler. If there is a secondary (emergency) pan, use that one.
2. Hang the float so it sits just above the bottom of the pan and moves freely. It should lift as soon as water collects.
3. Set the sensor body on a dry surface above the pan, away from where water could drip on it.
4. Units in a hot attic: the sensor is rated to about 122°F (50°C). Put the sensor body in the coolest spot the cable reaches.

4. Test the alert

1. Pour a small cup of water into the pan until the float lifts.
2. Confirm the sensor alarm sounds and your phone gets the alert.

3. Dry the pan. In the app, share the home with family or your home watch company so a second phone gets alerts.

> **No monthly fee.** YoLink says there are no required subscriptions and the app is free. Alerts arrive as push notifications and email. Phone alerts need the hub powered and the internet on; the sensor's local alarm works either way.

Monthly upkeep

When	What to do
Once a month	Place one Poesie tablet in the drain pan, as the label directs. Let it dissolve. Avoid contact with skin and eyes.
Before you leave for the season	Test the alert (step 4). Make sure the A/C is set to run, not off, so humidity stays under control.
Every 6–12 months	Have an AC technician check and clear the condensate line. Replace the sensor batteries when the app says they are low.

If you get an alert

1. Call your AC technician, or someone who can get inside the same day.
2. If water is near the top of the pan, turn the A/C off at the thermostat until the line is cleared.
3. In Martin County, FL? We can check the home. Email hello@homewatchtreasurecoast.com.

This kit alerts you; it does not shut off the A/C or clear a clogged line. Returns: unused items within 30 days, see homewatchtreasurecoast.com/shipping-returns.html. Questions: hello@homewatchtreasurecoast.com